



Product Data Sheet

Chrome In-Line Filter

T safe

t-safe.com



Chrome In-Line Filter



Features

- Sterilising grade 0.2 µm rated membrane filter
- High capacity filter with up to 92 day life cycle
- Compact design, enables installation in areas with restricted space
- Constant flow technology ensures optimal flow performance over life cycle
- Replacement filter cartridge system extends use and reduces overall cost
- Integral check valve prevents backflow contamination upstream

Order Information

Item	Code
Chrome In-Line Filter	02-803236
Replacement filter	02-000242

Technical Data

Max. operating pressure	5 bar
Max. operating temperature	60° C
Flow rate	12 L/min
Max. filter life cycle	92 days*
Connection	2 x ½ inch thread
Colour	Chrome

Microbial retention

Sterilising grade membrane filter, effective against all waterborne pathogens. Independently tested and validated in accordance with ASTM F838 against:

- *Legionella pneumophila*
- *Pseudomonas aeruginosa*
- *Brevundimonas diminuta*

Approvals

ASTM F838-15A, WRAS, KIWA, DVGW W270. Compliant with EU food and drinking water directives

* Dependent on local water quality and usage.

All information contained within this data sheet is based on the current knowledge and experience of T-safe. It is provided in good faith and is intended to serve only as a guideline for the selection and use of products. T-safe products should always be handled in accordance with the applicable Instruction for Use advice. The current data sheet is available at www.t-safe.com.